Technical data sheet

TCP Truss Clip

The TCP truss clip attaches girders, trusses and rafters to wall plates to provide wind restraint.

- TCP Truss Clips may be used for general purposes, strongback attachments as allpurpose ties wherever one member crosses another.
- Speed prong provides temporary attachment for ease of installation.
- Obround holes for easier nail driving.

Features

Features

Applications

Material

• Pre-galvanised mild steel



SIMPSON

Strong-Tie



TCP Truss Clip

Technical Data

TCP

References	Connector Dimensions [mm]					Header Holes	Joist Holes
	Α	В	C	D	t	Obround Ø4x6	Obround Ø4x6
TCP38	38	100	18	107	0.9	6	6
TCP47	47	100	23	107	0.9	6	6
TCP50	50	100	26	107	0.9	6	6

Performance Values

	Fasteners		Characteristic Capacity [kN]	Safe Working Loads [kN]
References	Truss	Wall Plate	R _{2,k}	R _{2, SWL, Short Term}
	Qty	Qty	N3.75x30	N3.75x30
ТСР	6	6	3.3	2.1

TCP

Truss Clip

Winchester Road Cardinal Point Tamworth Staffordshire B78 3HG tel: +44 1827 255600 fax: +44 1827 255616

Copyright by Simpson Strong-Tie® Information presented on this document is the exclusive property of Simpson Strong-Tie® It is valid only when associated with products supplied by Simpson Strong-Tie®

2024-01-18



SIMPSON Strong-Tie