


CBR Masonry Reinforcement Mesh

Provide added strength and stability.

- *Galvanised or stainless steel finish.*
- *Assists resistance to tensile stresses where settlement occurs. Easily incorporated into mortar course, coiled for ease of handling.*

Installation:

- *All metal components used in any particular application must be of the same material type.*
- *Gloves should be worn to protect hands from sharp metal edges.*
- *Position the mesh within the masonry bed joints, providing a minimum of 25mm cover to external faces.*
- *Overlap by a minimum of 75mm if joining two lengths together. The mesh can be laid every third brickwork course for most reinforcement.*



Features

Installation

- All metal components used in any particular application must be of the same material type.
- Gloves should be worn to protect hands from sharp metal edges.
- Position the mesh within the masonry bed joints, providing a minimum of 25 mm cover to external faces.
- Overlap by a minimum of 75 mm if joining two lengths together. The mesh can be laid every third brickwork course for most reinforcement.

CBR
Masonry Reinforcement Mesh

Technical Data

Product Dimensions

References	Material	Dimensions
CBR2063	Galvanised	63mm x 20m
CBR2063S	Stainless Steel	63mm x 20m
CBR20112	Galvanised	112mm x 20m
CBR20112S	Stainless Steel	112mm x 20m
CBR20175	Galvanised	175mm x 20m
CBR20175S	Stainless Steel	175mm x 20m
CBR20228	Galvanised	228mm x 20m
CBR20228S	Stainless Steel	228mm x 20m
CBR20305	Galvanised	305mm x 20m

Winchester Road Cardinal Point Tamworth Staffordshire B78
3HG
tel: +44 1827 255600
fax: +44 1827 255616

Copyright by Simpson Strong-Tie®

Information presented on this document is the exclusive property of Simpson Strong-Tie®
It is valid only when associated with products supplied by Simpson Strong-Tie®

CBR
Masonry Reinforcement
Mesh



www.strongtie.co.uk

SIMPSON**Strong-Tie**

2024-01-19